

Order No.: 5LZ911731A | GTIN (EAN): 4058352692899

Product description: DA2,psh.bttm.interf,lokCtrlcentCtrl



DALI2push button interface, slave, local control, central control, dimmable, installation type: recessed, installation location: in the switch box, of plastic, protection rating (complete): IP20, certification: CE, 4 x push button input, 1 x DALI-2, packaging unit: 1 piece

IP 20

Wt. (kg): 0.1
GTIN (EAN): 4058352692899

Order No.: 5LZ911731A | GTIN (EAN): 4058352692899

Detailed technical description: DA2,psh.bttf.interf,lokCtrlcentCtrl



Key data

- System family: Siteco Connect 11, SITECO Connect 22
- Product type: lighting management components
- Product name: DALI2
- Order No.: 5LZ911731A

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Temperature range (operation): -20..+75°C
- Certification, designation: CE

Material, Colour

- housing: plastic, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only suitable for indoor use

Dimensions, Weight

- Length: 41mm
- Width: 28mm
- Height: 14mm
- Weight: 0.1kg

Inputs

4x push button input

- Connection: plug-in terminal, 2-pole, max. 1.5mm²
- Feature: zero-potential

Outputs

1x DALI-2

- Connection: plug-in terminal, 2-pole, max. 1.5mm²
- System current: DALI current 2mA