


Order No.: 5NY231645KM08 | **GTIN (EAN):** 4039806381347

Product description: mast,con.rd,steel,powd,DB702S,4.5m,Ø60



mast, mast, conical round, of steel, powder-coated, Siteco® metallic grey (DB 702S), height: 4.5m, spigot size: 60mm (post-top), planted section: h= 800mm / Ø= 134mm, standard: DIN EN 40, packaging unit: 1 piece

Wt. (kg): 26.2
GTIN (EAN): 4039806381347




It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5NY231645KM08 | **GTIN (EAN):** 4039806381347

Detailed technical description: mast,con.rd,steel,powd,DB702S,4.5m,Ø60



Key data

- Product type: mast
- Product name: mast
- Order No.: 5NY231645KM08

Certificates, Standards

- Standard: DIN EN 40

Material, Colour


- mast: steel, powder-coated, Siteco® metallic grey (DB 702S), conical round
- Colour specification: Siteco® metallic grey (DB 702S)

Dimensions, Weight

- Height: 4.5m
- Weight: 26.2kg
- Mast spigot: spigot size: 60mm
- Planted section: h= 800mm / Ø= 134mm

Order No.: 5NY231645KM08 | **GTIN (EAN):** 4039806381347

Dimensions: mast,con.rd,steel,powd,DB702S,4.5m,Ø60



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -