


Order No.: 51WD107AG1AS | **GTIN (EAN):** 4058352520956


Product description: Rond41S,1350lm830/840,0/1,PMMA,sens,wh



Rondel 41-S, wall and ceiling luminaire, primary optical cover: enclosure, of PMMA, opal, light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, LED, rated luminous flux: 1.350lm, luminous efficacy: 96lm/W, light colour: 830/840, colour temperature: 3000/4000K, control gear: ECG, with terminal, 3-pole, max. 2.5mm², mains connection: 230V, AC, 50/60Hz, rated input power: 14W, luminaire housing, round, of steel, powder-coated, white, diameter: 280mm, height: 100mm, brightness and presence sensor, HF sensor, protection rating (complete): IP44, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, permissible operating ambient temperature: -20..+40°C, permissible storage temperature: -30..+80°C, packaging unit: 1 piece


IP 44  

Lamps:	LED
Wt. (kg):	0.6
GTIN (EAN):	4058352520956



Order No.: 51WD107AG1AS | GTIN (EAN): 4058352520956

Detailed technical description: Rond41S,1350lm830/840,0/1,PMMA,sens,wh



Key data

- Product type: wall and ceiling luminaire
- Product name: Rondel 41-S
- Order No.: 51WD107AG1AS

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: enclosure, opal
- Beam angle: diffuse distribution
- Symmetry: symmetric
- Light emission: direct distribution

Lamps:

- Lamps: with LED
- Rated luminous flux: 1350lm
- Luminous efficacy: 96lm/W
- Colour temperature: 3000/4000K
- Colour rendering index: CRI > 80
- Light colour: 830/840
- SDCM (Standard Deviation of Colour Matching): MacAdam \leq 5 SDCM (initial)
- Rated input power: 14W
- Supplement: colour temperature can be selected via DIP switch

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP44
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Material, Colour

- luminaire housing: steel, powder-coated, white, round
- Colour specification: white
- Cover: enclosure of PMMA

Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling, to the wall
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 3-pole, max. 2.5mm²
- Nominal voltage: 230V, 220..240V, 50/60Hz, AC

Dimensions, Weight


- Diameter: 280mm
- Height: 100mm
- Weight: 0.6kg

Service life

- Rated service life: 50000h (L80/B10) at AT = 25°C

Order No.: 51WD107AG1AS | GTIN (EAN): 4058352520956

Dimensions: Rond41S,1350lm830/840,0/1,PMMA,sens,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -