

## Order No.: 59HL94002 | GTIN (EAN): 4058352379349 Product description: HB11basemod,surf



Highbay 11Interface S, slave, local control, central control, dimmable, installation type: surface-mounted, installation location: to the luminaire, of plastic, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, 1 x 1 x DALI-2, packaging unit: 1 piece

IP 54 🔲 🤆

Wt. (kg): 0.3 GTIN (EAN): 405

4058352379349

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 05.01.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

# siteco

### Order No.: 59HL94002 | GTIN (EAN): 4058352379349 Detailed technical description: HB11basemod,surf



#### Key data

- System family: Siteco Connect 11, SITECO Connect 22
- Product type: base module
- Product name: Highbay 11
- Order No.: 59HL94002

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### **Operating device:**

- Control: DALI 2, dimmable

#### **Certificates, Standards**

- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+50°C
- Certification, designation: CE

#### Material, Colour

- housing: plastic, white, square
- Colour specification: white
- mounting bracket: steel, galvanised

#### Mounting

- Mounting method, mounting location: surface-mounted, to the luminaire
- Supplement: only suitable for indoor use

#### Dimensions, Weight

- Length: 83mm
- Width: 83mm
- Height: 28mm
- Weight: 0.3kg

#### Outputs

- 1x DALI-2
- Feature: DALI, slave function, DALI current max. 6mA