

Order No.: 5WD26CDC3CN3 | **GTIN (EAN):** 4058352315804


Product description: TL33Cmn,18400lm750,DA,TSG



TL 33C mini, tunnel luminaire, primary light control with counter beam optics, primary optical cover: cover panel, of toughened safety glass, non-reflecting, transparent, light emission: direct distribution, primary light characteristic: asymmetric, installation type: surface-mounted, connection on control gear side, LED, High Power LED, rated luminous flux: 18.400lm, luminous efficacy: 143lm/W, light colour: 750, colour temperature: 5000K, control gear: DALI, with system connector, mains connection: 220..240V, AC, 50/60Hz, connection cable plug integrated into luminaire housing at face end, rated input power: 129W, connection on mains side, 7-pole, max. 10mm² (5G+2), with terminal, luminaire housing, of stainless steel 1.4404 (AISI316), etched and passivated, length: 390mm, width: 295mm, height: 68mm, heat sink, of Al Mg 2, e-box, of stainless steel 1.4404 (AISI316), etched and passivated, length: 510mm, width: 213mm, height: 115mm, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK09, permissible operating ambient temperature: -25..+45°C, packaging unit: 1 piece

IP 66 IK 09  

Lamps:	LED
Wt. (kg):	10.8
GTIN (EAN):	4058352315804



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5WD26CDC3CN3 | **GTIN (EAN):** 4058352315804

Detailed technical description: TL33Cmn,18400lm750,DA,TSG



Key data

- Product type: tunnel luminaire
- Product name: TL 33C mini
- Order No.: 5WD26CDC3CN3

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: counter beam optics
- Cover: cover panel, transparent, non-reflecting
- Symmetry: asymmetric distribution
- Light emission: direct distribution

Lamps:

- Supplement: suitable for 3-phase through-wiring on mains side

Operating device:

- Control gear: ECG DALI
- Control: DALI

Component 2

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK09
- Temperature range (operation): -25...+45°C
- Certification, designation: CE

Material, Colour

- luminaire housing: stainless steel 1.4404 (AISI316), etched and passivated
- e-box: stainless steel 1.4404 (AISI316), etched and passivated
- Cover: cover panel of toughened safety glass

Mounting

- Mounting method, mounting location: surface-mounted, to supporting structure, to the ceiling

Electrical connection

- Connection: system connector
- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: 10kV 1.2/50µs
- Connection cable: plug integrated into luminaire housing at face end

Dimensions, Weight


- Length: 390mm
- Width: 295mm
- Height: 68mm
- Weight: 10.8kg

Service life

- Rated service life: 100000h (L95/B10) at AT = 25°C

Order No.: 5WD26CDC3CN3 | **GTIN (EAN):** 4058352315804

Dimensions: TL33Cmn,18400lm750,DA,TSG



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5WD26CDC3CN3 | **GTIN (EAN):** 4058352315804

Planning data: TL33Cmn,18400lm750,DA,TSG


5WD26CDC3CN3: 1x LED

4058352315804

5WD26CDC3CN3

LED 5000 K | CRI ≥ 70

Φ_V 18400 lm



— C 0/180

- - - C 90/270

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -