

Order No.: 5LZ960100 | GTIN (EAN): 4058352651612

Product description: SCon21B,controller,centCtrl,netw.ETH



SITECO Connect 21Bcontroller, master, central control, dimmable, installation type: recessed, installation location: in an electrical distributor, part units: 12 part units, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, voltage: 100..240V, voltage type: AC, 1 x network connector Ethernet, 1 x USB/WiFi, 3 x service push button, 2 x DALI-2, 1 x status LED, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.2
GTIN (EAN): 4058352651612

Order No.: 5LZ960100 | GTIN (EAN): 4058352651612

Detailed technical description: SCon21B,controller,centCtrl,netw.ETH



Key data

- System family: SITECO Connect 21B
- Product type: lighting management components
- Product name: SITECO Connect 21B
- Order No.: 5LZ960100

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Mounting

- Mounting method, mounting location: recessed, in an electrical distributor
- Supplement: only suitable for indoor use

Electrical connection

- Connection: terminal, 2-pole, max. 1.5mm²
- Nominal voltage: 100..240V, 50/60Hz, AC

Dimensions, Weight

- Weight: 0.2kg

Inputs

3x service push button

- Option: for manual control and basic system setting

Outputs

2x DALI-2

- Connection: screw terminal, 2-pole, max. 1.5mm²
- System current: DALI current 250mA per DALI line
- Feature: maximum 64 ECG DALI and maximum 63 certified DALI2 sensors/push button interfaces connectable per DALI line, HCLlive function in combination with ECG DT8, averaging with connected light sensors, connection of DALI2 certified sensors