

Order No.: 5DTAXTS43001 | GTIN (EAN): 4050737845258 Product description: AXT,3ph-tr,spsurf,gy,L3000,0/1



AX T, 3-phase track, installation type: suspended mounting, surface-mounted, control gear: ON/OFF, mains connection: 220..240V/380..400V, AC, of extruded aluminium section, coated, grey, length: 3.000mm, width: 32mm, height: 33mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, packaging unit: 1 piece

∰ IP 20 🛓 (€

Wt. (kg): GTIN (EAN): 2.4 4050737845258

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5DTAXTS43001 | GTIN (EAN): 4050737845258 Detailed technical description: AXT,3ph-tr,spsurf,gy,L3000,0/1



Key data

- Product type: 3-phase track
- Product name: AX T
- Order No.: 5DTAXTS43001

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: max. 16A

Operating device:

Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I
 - (protective earthing)
- Certification, designation: CE, ENEC

Material, Colour

- Colour specification: grey
- Mounting
- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling

Electrical connection

 Nominal voltage: 220..240V/380..400V, AC

Dimensions, Weight

- Length: 3000mm
- Width: 32mm
- Height: 33mm
- Weight: 2.4kg