

Order No.: 5LS31321EK | **GTIN (EAN):** 4039806171931

Product description: FR100FR200FR500,TW,5x2.5²,L1.4m,term



FR 100FR 200FR 500, through-wiring, installation type: recessed, through-wiring set, 5-core, 2.5mm², cable length: 1,4m, terminal, 5-pole, max. 2.5mm², with protective earth, insulation class (complete): insulation class I (protective earthing), packaging unit: 1 piece



Wt. (kg): 0.3
GTIN (EAN): 4039806171931

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5LS31321EK | **GTIN (EAN):** 4039806171931

Detailed technical description: FR100FR200FR500,TW,5x2.5²,L1.4m,term



Key data

- Product type: through-wiring
- Product name: FR 100, FR 200, FR 500
- Order No.: 5LS31321EK

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: for through-wiring within a luminaire, through-wiring set includes heat-resistant single-core cable, terminals and mounting hardware

Certificates, Standards

- Insulation class: insulation class I (protective earthing)

Mounting

- Mounting method, mounting location: recessed, in the luminaire housing
- Arrangement: interrupted trunking
- Supplement: wiring from one luminaire to the next is with standard cable (e.g. NYM)

Dimensions, Weight

- Weight: 0.3kg