

**Order No.:** 5LZ902050TW | **GTIN (EAN):** 4058352145807


**Product description:** SCon41Rotrot.dimmm,rot/push-bttn,rec



SITECO Connect 41 Rotaryrotary dimmer, master, local control - self-sufficient standalone sensors, dimmable, installation type: recessed, installation location: in the switch box, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 230V, voltage type: AC, 1 x rotary button/push button, 1 x DALI, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1  
GTIN (EAN): 4058352145807



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5LZ902050TW | **GTIN (EAN):** 4058352145807

**Detailed technical description:** SCon41Rotrot.dimm,rot/push-bttn,rec



#### Key data

- System family: SITECO Connect 41
- Product type: rotary dimmer
- Product name: SITECO Connect 41 Rotary
- Order No.: 5LZ902050TW

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: DALI, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -5...+45°C
- Certification, designation: CE

#### Material, Colour

- installation housing: plastic, grey
- Colour specification: grey

#### Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only suitable for use in indoor areas

#### Electrical connection

- Nominal voltage: 230V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 80mm
- Width: 80mm
- Height: 32mm
- Weight: 0.1kg

#### Inputs

#### 1x rotary button/push button

- Connection: screw terminal, 2-pole, max. 4.0mm<sup>2</sup>

#### Outputs

#### 1x DALI

- Connection: screw terminal, 2-pole, max. 4mm<sup>2</sup>
- Limiting: max. 25x ECG DALI
- Feature: ON/OFF, bright/dark, storing of brightness power on illumination levels, expansion of control units or number of ECG DALI via parallel switching of several rotary potentiometers; incl. rotary button and frame of white plastic
- Cable length: max. 300m

**Order No.:** 5LZ902050TW | **GTIN (EAN):** 4058352145807

**Dimensions:** SCon41Rotrot.dimmm,rot/push-bttn,rec

