


Order No.: 5MN91402 | **GTIN (EAN):** 4050737755007

Product description: Vega11 passepartout,dir/ind




Vega® 11, passepartout, light emission: direct/indirect distribution, passepartout, for luminaire, packaging unit: 1 piece

Wt. (kg): 0.5
GTIN (EAN): 4050737755007

4050737963761 + 4050737755007

5MN238DLC + 5MN91402

LED 4000K / CRI ≥ 80 Φ_{N} 4240 lm




It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5MN91402 | **GTIN (EAN):** 4050737755007

Detailed technical description: Vega11 passepartout,dir/ind



Key data

- Product type: passepartout
- Product name: Vega® 11
- Order No.: 5MN91402

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light emission: direct/indirect distribution, 70:30

Dimensions, Weight

- Weight: 0.5kg


Order No.: 5MN91402 | GTIN (EAN): 4050737755007

Planning data: Vega11passepourtout,dir/ind

5MN238DLC + 5MN91402: 1x
LED 4000K / CRI ≥ 80

4050737963761 + 4050737755007
5MN238DLC + 5MN91402

LED 4000K / CRI ≥ 80 ϕ_N 4240 lm



No. of luminaires in room
Reflection factors 70/50/20

Em(lx)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m²	0.8	0.9	1.6	1.8	4.1	4.6
30 m²	1.2	1.3	2.4	2.6	6.1	6.6
40 m²	1.5	1.7	3.0	3.3	7.5	8.3
50 m²	1.8	2.0	3.6	3.9	9.1	9.9
75 m²	2.7	2.8	5.4	5.7	14	14
100 m²	3.5	3.7	6.9	7.3	17	18
500 m²	15	16	31	32	77	80


Maintenance factor 0.8

Rh = Lh + 0.5 m

5MN238DLC003 + 5MN91402:
1x LED 3000K / CRI ≥ 80

4050737964164 + 4050737755007
5MN238DLC003 + 5MN91402

LED 3000K / CRI ≥ 80 ϕ_N 4250 lm



No. of luminaires in room
Reflection factors 70/50/20

Em(lx)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m²	0.8	0.9	1.6	1.8	4.1	4.6
30 m²	1.2	1.3	2.4	2.6	6.1	6.6
40 m²	1.5	1.6	3.0	3.3	7.5	8.2
50 m²	1.8	2.0	3.6	3.9	9.1	9.8
75 m²	2.7	2.8	5.4	5.7	14	14
100 m²	3.5	3.7	6.9	7.3	17	18
500 m²	15	16	31	32	77	79


Maintenance factor 0.8

Rh = Lh + 0.5 m

5MN238DLC0S + 5MN91402:
1x LED 4000K / CRI ≥ 80

4050737964041 + 4050737755007
5MN238DLC0S + 5MN91402

LED 4000K / CRI ≥ 80 ϕ_N 4240 lm



No. of luminaires in room
Reflection factors 70/50/20

Em(lx)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m ²	0.8	0.9	1.6	1.8	4.1	4.6
30 m ²	1.2	1.3	2.4	2.6	6.1	6.6
40 m ²	1.5	1.7	3.0	3.3	7.5	8.3
50 m ²	1.8	2.0	3.6	3.9	9.1	9.9
75 m ²	2.7	2.8	5.4	5.7	14	14
100 m ²	3.5	3.7	6.9	7.3	17	18
500 m ²	15	16	31	32	77	80

Maintenance factor 0.8

Rh = Lh + 0.5 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -


Order No.: 5MN91402 | GTIN (EAN): 4050737755007

Planning data: Vega11passepourtout,dir/ind

5MN238DLE + 5MN91402: 1x
LED 4000K / CRI ≥ 80

4050737964188 + 4050737755007
5MN238DLE + 5MN91402

LED 4000K / CRI ≥ 80 ϕ_N 8030 lm



No. of luminaires in room

Reflection factors 70/50/20

Em(x)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m²	0.4	0.5	0.9	1.0	2.1	2.4
30 m²	0.6	0.7	1.3	1.4	3.2	3.5
40 m²	0.8	0.9	1.6	1.7	4.0	4.4
50 m²	1.0	1.0	1.9	2.1	4.8	5.2
75 m²	1.4	1.5	2.9	3.0	7.2	7.5
100 m²	1.8	1.9	3.7	3.9	9.2	9.7
500 m²	8.2	8.4	16	17	41	42


Maintenance factor 0.8

Rh = Lh + 0.5 m

5MN238DLE003 + 5MN91402:
1x LED 3000K / CRI ≥ 80

4050737963846 + 4050737755007
5MN238DLE003 + 5MN91402

LED 3000K / CRI ≥ 80 ϕ_N 7210 lm



No. of luminaires in room

Reflection factors 70/50/20

Em(lx)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m²	0.5	0.5	1.0	1.1	2.4	2.7
30 m²	0.7	0.8	1.4	1.6	3.6	3.9
40 m²	0.9	1.0	1.8	1.9	4.4	4.9
50 m²	1.1	1.2	2.1	2.3	5.4	5.8
75 m²	1.6	1.7	3.2	3.3	8.0	8.4
100 m²	2.0	2.2	4.1	4.3	10	11
500 m²	9.1	9.4	18	19	46	47


Maintenance factor 0.8

Rh = Lh + 0.5 m

5MN238DLE0S + 5MN91402:
1x LED 4000K / CRI ≥ 80

4050737963747 + 4050737755007
5MN238DLE0S + 5MN91402

LED 4000K / CRI ≥ 80 ϕ_N 8030 lm



No. of luminaires in room

Reflection factors 70/50/20

Em(lx)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m²	0.4	0.5	0.9	1.0	2.1	2.4
30 m²	0.6	0.7	1.3	1.4	3.2	3.5
40 m²	0.8	0.9	1.6	1.7	4.0	4.4
50 m²	1.0	1.0	1.9	2.1	4.8	5.2
75 m²	1.4	1.5	2.9	3.0	7.2	7.5
100 m²	1.8	1.9	3.7	3.9	9.2	9.7
500 m²	8.2	8.4	16	17	41	42

Maintenance factor 0.8

Rh = Lh + 0.5 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5MN91402 | **GTIN (EAN):** 4050737755007


Planning data: Vega11passepartout,dir/ind

5MN238DLE0S3 + 5MN91402:
1x LED 3000K / CRI ≥ 80

4050737964263 + 4050737755007

5MN238DLE0S3 + 5MN91402

LED 3000K / CRI ≥ 80 Φ_H 7210 lm



No. of luminaires in room

Reflection factors 70/50/20

Em(x)	100		200		500	
Lh(m)	2.5	3.0	2.5	3.0	2.5	3.0
20 m²	0.5	0.5	1.0	1.1	2.4	2.7
30 m²	0.7	0.8	1.4	1.6	3.6	3.9
40 m²	0.9	1.0	1.8	1.9	4.4	4.9
50 m²	1.1	1.2	2.1	2.3	5.4	5.8
75 m²	1.6	1.7	3.2	3.3	8.0	8.4
100 m²	2.0	2.2	4.1	4.3	10	11
500 m²	9.1	9.4	18	19	46	47

Maintenance factor 0.8

Rh = Lh + 0.5 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com