

Order No.: 5TR36000H | GTIN (EAN): 4039806557940 Product description: Mod,bl-ins,steel,sr,4su



Modario[®], blank insert, of steel, coated, metallic grey (RAL 9006), blank insert, of steel, coated, metallic grey (RAL 9006), length: 1.196mm, width: 48mm, 4x system unit, system units: 299mm, for laboratory/development/technical college, storage/logistics, installation/production/process, special areas/ancillary areas, retail/exhibition room, protection rating (complete): for IP20 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

() (€

Wt. (kg): GTIN (EAN): 0.5 4039806557940

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 10.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5TR36000H | GTIN (EAN): 4039806557940 Detailed technical description: Mod,bl-ins,steel,sr,4su



Key data

- Product type: blank insert
- Product name: Modario®
- Order No.: 5TR36000H

Certificates, Standards

- Protection rating: for IP20 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- blank insert: steel, coated, metallic grey (RAL 9006), 4x system unit
- Colour specification: metallic grey (RAL 9006)
- blank insert: steel, coated, metallic grey (RAL 9006)
- Quantity: 4 piece
- Colour specification: metallic grey (RAL 9006)

Dimensions, Weight

- System units: 4x SE
- Length: 1196mm
- Width: 48mm
- Weight: 0.5kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 10.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -