

**Order No.:** 56TL1CRM0B | **GTIN (EAN):** 4058352595497

**Product description:** Licrepea,DALI,rec



Licross®repeater, master, local control, central control, dimmable, installation type: recessed, installation location: to the Licross® trunking rail, of sheet steel, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, voltage: 230V, voltage type: AC, 1 x DALI, service push button, 1 x DALI, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.3  
GTIN (EAN): 4058352595497

Order No.: 56TL1CRM0B | GTIN (EAN): 4058352595497

Detailed technical description: Licrepea,DALI,rec



#### Key data

- System family: SITECO Connect 41
- Product type: repeater
- Product name: Licross®
- Order No.: 56TL1CRM0B

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Lamps:

- Supplement: halogen-free wiring

##### Operating device:

- Control: DALI, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -20..+60°C
- Certification, designation: CE, UKCA

#### Material, Colour

- trunking rail adapter set: sheet steel, coil coated, white
- Colour specification: white

#### Mounting

- Mounting method, mounting location: recessed, to the Licross® trunking rail
- Supplement: only suitable for indoor use

#### Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50Hz, AC

#### Dimensions, Weight

- Weight: 0.3kg

#### Outputs

##### 1x DALI

- Feature: DALI, master function, broadcast addressing, max. 64 DALI ECGs