

Order No.: 59TL3FTE | **GTIN (EAN):** 4058352340110

Product description: Lic-feedout,L450,14x2.5²,IP40,bk



Licross® feed-out, matt jet black (RAL 9005); wiring trunking rail element of sheet steel, galvanised, coated, with cable entry for four cables, Ø 8.5..13mm; 2x end cap of PC, jet black (RAL 9005), with cable entry for one cable, Ø ≤13mm (from above) or one cable, Ø ≤20mm (on face end); blank cover of PC/ABS, jet black (RAL 9005); connector of steel, galvanised, connector pre-assembled on trunking rail; connection via terminal, 14-pole, 1.5..2.5mm², internal wiring halogen-free; dimension: (LxWxH) = 450 x 64 x 67mm; for IP20/IP40 protection rating; insulation class: insulation class I (protective earthing); certification: CE, UKCA; packaging unit: 1 piece



Wt. (kg): 0.8
GTIN (EAN): 4058352340110

Order No.: 59TL3FTE | **GTIN (EAN):** 4058352340110

Detailed technical description: Lic-feedout,L450,14x2.5²,IP40,bk



Key data

- Product type: feed-out
- Product name: Licross®
- Order No.: 59TL3FTE

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: for connection on rail side

Component 2

Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail element: sheet steel, galvanised, coated, matt jet black (RAL 9005)
- Colour specification: matt jet black (RAL 9005)
- end cap: PC, jet black (RAL 9005)
- Quantity: 2 piece
- Colour specification: jet black (RAL 9005)
- blank cover: PC/ABS, jet black (RAL 9005)
- Colour specification: jet black (RAL 9005)
- connector: steel, galvanised, connector pre-assembled on trunking rail

Electrical connection

- Connection: terminal, 14-pole, 1.5..2.5mm²
- Through-wiring: 14x 2.5mm²

Dimensions, Weight

- Length: 450mm
- Width: 64mm
- Height: 67mm
- Weight: 0.8kg