

**Order No.:** 59TL3FT7 | **GTIN (EAN):** 4058352340080

**Product description:** Lic-feedout,L300,7x2.5<sup>2</sup>,IP40,bk




Licross® feed-out, matt jet black (RAL 9005); wiring trunking rail element of sheet steel, galvanised, coated, with cable entry for two cables, Ø 8.5..13mm; 2x end cap of PC, jet black (RAL 9005), with cable entry for one cable, Ø ≤13mm (from above) or one cable, Ø ≤20mm (on face end); blank cover of PC/ABS, jet black (RAL 9005); connector of steel, galvanised, connector pre-assembled on trunking rail; connection via terminal, 7-pole, 1.5..2.5mm<sup>2</sup>, internal wiring halogen-free; dimension: (LxWxH) = 300 x 64 x 67mm; for IP20/IP40 protection rating; insulation class: insulation class I (protective earthing); certification: CE, UKCA; packaging unit: 1 piece



Wt. (kg): 0.7  
GTIN (EAN): 4058352340080

**Order No.:** 59TL3FT7 | **GTIN (EAN):** 4058352340080

**Detailed technical description:** Lic-feedout,L300,7x2.5<sup>2</sup>,IP40,bk



#### Key data

- Product type: feed-out
- Product name: Licross®
- Order No.: 59TL3FT7

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Lamps:

- Supplement: for connection on rail side

#### Component 2

#### Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, UKCA

#### Material, Colour

- trunking rail element: sheet steel, galvanised, coated, matt jet black (RAL 9005)
- Colour specification: matt jet black (RAL 9005)
- end cap: PC, jet black (RAL 9005)
- Quantity: 2 piece
- Colour specification: jet black (RAL 9005)
- blank cover: PC/ABS, jet black (RAL 9005)
- Colour specification: jet black (RAL 9005)
- connector: steel, galvanised, connector pre-assembled on trunking rail

#### Electrical connection

- Connection: terminal, 7-pole, 1.5..2.5mm<sup>2</sup>
- Through-wiring: 7x 2.5mm<sup>2</sup>

#### Dimensions, Weight

- Length: 300mm
- Width: 64mm
- Height: 67mm
- Weight: 0.7kg