

**Order No.:** 5EA40EH01 | **GTIN (EAN):** 4058352450178

**Product description:** SConWi,SmartPlugMotionHigh



SITECO Connect WirelessSmart Plug Motion High, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, 2.4GHz, local mesh radio network, D4i, local setting and operation with USB stick, by daylight, by movement, manual, by time, by timer, by weekday, via API, optionally via radio push button, 1 PIR movement sensor, daylight sensor, temperature sensor, inclination sensor, PIR movement sensor, brightness sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352450178

**Order No.:** 5EA40EH01 | **GTIN (EAN):** 4058352450178

**Detailed technical description:** SConWi,SmartPlugMotionHigh



#### Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40EH01

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: D4i, Smart Interface below

#### Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+85°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: plastic, transparent, colour-backed, dark grey
- Colour specification: dark grey

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 6..12m

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Weight: 0.1kg

#### Inputs

#### PIR movement sensor

- Detection range: D max. 18m

Order No.: 5EA40EH01

Dimensions: SConWi, Sma

Mounting height	X axis	Y axis
7.0 m	11.9 m	12.4 m
8.0 m	13.6 m	14.2 m
9.0 m	15.3 m	15.9 m
10.0 m	17.0 m	17.7 m