ѕітесо

Order No.: 5EA40LH01 | GTIN (EAN): 4058352450239 Product description: SConWi,MotionHigh





SITECO Connect WirelessMotion High, sensor, communication: Bluetooth, D4i type A, control: local setting and operation with smartphone app, by daylight, by movement, sensor technology: 1 PIR movement sensor, daylight sensor, Smart Interface below, setting of the ECG to logarithmic DALI dimming required, Compatible only with ECGs with logarithmic DALI dimming curve, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, PIR movement sensor, protection rating (complete): IP66, certification: CE, UKCA, packaging unit: 1 piece

IP 66 IK 09 CE

Wt. (kg): 0.1 GTIN (EAN): 4058352450239

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 5EA40LH01 | GTIN (EAN): 4058352450239 Detailed technical description: SConWi,MotionHigh



- System family: SITECO Connect 31
- Product type: sensor
- Product name: SITECO Connect
- Order No.: 5EA40LH01

Lighting technology | Lamps | Control

Component 1

Operating device:

 Control: D4i, Smart Interface below, setting of the ECG to logarithmic DALI dimming required, Compatible only with ECGs with logarithmic DALI dimming curve

Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -40..+70°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

Material, Colour

- housing: plastic, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 4..12m

Electrical connection

- Nominal voltage: 24V, DC

Dimensions, Weight

Weight: 0.1kg

Inputs


PIR movement sensor

- Detection range: max. ø30m
- Feature: incl. shield for reducing detection area

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 5EA40LH01 | GTIN (EAN): 4058352450239 Dimensions: SConWi,MotionHigh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com