

Order No.: 5EA40LH01 | GTIN (EAN): 4058352450239

Product description: SConWi,MotionHigh



SITECO Connect Wireless, Motion High, Smart Interface below, setting of the ECG to logarithmic DALI dimming required, installation type: screw fastening, installation location: to the luminaire, of plastic, protection rating (complete): IP66, certification: CE, UKCA, voltage: 24V, voltage type: DC, PIR movement sensor, packaging unit: 1 piece

IP 66 CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352450239

Order No.: 5EA40LH01 | GTIN (EAN): 4058352450239

Detailed technical description: SConWi,MotionHigh



#### Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40LH01

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: D4i

#### Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -40..+70°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

#### Material, Colour

- housing: plastic, grey
- Colour specification: grey

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 4..12m

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Weight: 0.1kg

#### Inputs

#### PIR movement sensor

- Detection range: D max. 30m
- Feature: incl. shield for reducing detection area

Order No.: 5EA40LH01

Dimensions: SConWi, Motion

Y axis



| Mounting height | X axis | Y axis |
|-----------------|--------|--------|
| 4.6 m           | 12.0 m | 12.0 m |
| 8.0 m           | 24.0 m | 24.0 m |
| 12.0 m          | 30.0 m | 30.0 m |

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 15.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -