

## Order No.: 59TR6CT | GTIN (EAN): 4058352487129 Product description: Lic-T-conn,L300,IP40,sr(w/o.wiring)



Licross®, T-connector, trunking rail element, of steel, galvanised, coated, metallic grey (RAL 9006), length: 300mm, width: 197mm, height: 67mm, blank cover, of PC/ABS, metallic grey (RAL 9006), connector, of steel, galvanised, protection rating (complete): for IP20/IP40 protection rating, certification: CE, UKCA, packaging unit: 1 piece

Œ

Wt. (kg): 2.0 GTIN (EAN):

4058352487129

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

# ѕітесо

## Order No.: 59TR6CT | GTIN (EAN): 4058352487129 Detailed technical description: Lic-T-conn,L300,IP40,sr(w/o.wiring)



#### Key data

- Product type: T-connector
- Product name: Licross®
- Order No.: 59TR6CT

#### Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Certification, designation: CE, UKCA

#### Material, Colour

- trunking rail element: steel, galvanised, coated, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)
- blank cover: PC/ABS, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)
- connector: steel, galvanised, connector pre-assembled on trunking rail
- Quantity: 3 piece

#### Mounting

 Supplement: with safety hook (with height adjustment), Ø 6mm, for suspension at central node

### Dimensions, Weight

- Length: 300mm
- Width: 197mm
- Height: 67mm
- Weight: 2.0kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -