

Order No.: 59TR3CX | GTIN (EAN): 4058352485415 Product description: Lic-X-conn,L300,IP40,bk(w/o.wiring)



Licross®, X-connector, trunking rail element, of steel, galvanised, coated, matt jet black (RAL 9005), length: 300mm, width: 300mm, height: 67mm, blank cover, of PC/ABS, jet black (RAL 9005), connector, of steel, galvanised, protection rating (complete): for IP20/IP40 protection rating, certification: CE, UKCA, packaging unit: 1 piece

ĆE


Wt. (kg): 3.0 GTIN (EAN):

4058352485415

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 59TR3CX | GTIN (EAN): 4058352485415 Detailed technical description: Lic-X-conn,L300,IP40,bk(w/o.wiring)



Key data

- Product type: X-connector
- Product name: Licross®
- Order No.: 59TR3CX

Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Certification, designation: CE, UKCA

Material, Colour

- trunking rail element: steel, galvanised, coated, matt jet black (RAL 9005)
- Colour specification: matt jet black (RAL 9005)
- blank cover: PC/ABS, jet black (RAL 9005)
- Colour specification: jet black (RAL 9005)
- connector: steel, galvanised, connector pre-assembled on trunking rail
- Quantity: 4 piece

Mounting

 Supplement: with safety hook (with height adjustment), Ø 6mm, for suspension at central node

Dimensions, Weight

- Length: 300mm
- Width: 300mm
- Height: 67mm
- Weight: 3.0kg