

Order No.: 5XA779220000BA | **GTIN (EAN):** 4058352557112

Product description: FL11mxpro,ECG-unit,Lo,DMX+RDM,IC1



Floodlight FL 11 maxi pro ECG unit; brightness control: DMX+RDM; with terminal, 8-pole, max. 2.5mm², mains connection: 220..240V/380..400V AC, surge voltage resistance: line to ground: 10kV, ECG unit ECG unit of diecast aluminium, uncoated natural; length: 500mm / width: 152mm / height: 77mm; equipment: Longlife, insulation class (complete): insulation class I (protective earthing); certification: CE; permissible storage temperature: -40..+85°C packaging unit: 1 piece



Wt. (kg): 5.6
GTIN (EAN): 4058352557112

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5XA779220000BA | **GTIN (EAN):** 4058352557112

Detailed technical description: FL11mxpro,ECG-unit,Lo,DMX+RDM,IC1



Key data

- Product type: ECG unit
- Product name: Floodlight FL 11 maxi pro
- Order No.: 5XA779220000BA

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DMX+RDM

Certificates, Standards

- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- ECG unit: diecast aluminium, uncoated, natural
- Colour specification: natural

Electrical connection

- Connection: terminal, 8-pole, max. 2.5mm²
- Nominal voltage: 220..240V/380..400V, AC
- Surge voltage resistance: line to ground: 10kV

Dimensions, Weight

- Length: 500mm
- Width: 152mm
- Height: 77mm
- Weight: 5.6kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -