
siteco

Order No.: 51MQ14WD2312 | **GTIN (EAN):** 4058352490518

Product description: APO21l,1245x307,3800lm830,DA,IP50,wh





Apollon 21 linear, office luminaire, primary optical cover: micro prismatic cover, CAT 2 (L≤ 3000cd/m²), light emission: direct distribution, primary light characteristic: symmetric, installation type: lay-in mounting, recessed, LED, rated luminous flux: 3.800lm, luminous efficacy: 115lm/W, light colour: 830, colour temperature: 3000K, control gear: DALI, with terminal, 5-pole, mains connection: 220..240V, AC, 50/60Hz, rated input power: 33W, housing, of aluminium, coated, pure white, length: 1.245mm, width: 307mm, height: 30mm, housing upper side, of sheet steel, galvanised, protection rating (complete): IP20, protection rating (lamp compartment, on room side): IP50, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, packaging unit: 1 piece

IP 20

Lamps:	LED
Wt. (kg):	3.0
GTIN (EAN):	4058352490518


It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 17.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 51MQ14WD2312 | **GTIN (EAN):** 4058352490518

Detailed technical description: APO21l,1245x307,3800lm830,DA,IP50,wh



Key data
- Product type: office luminaire
- Product name: Apollon 21 linear
- Order No.: 51MQ14WD2312

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:
- Cover: micro prismatic cover
- Beam angle: wide distribution, 90°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 19

Lamps:
- Lamps: with LED
- Rated luminous flux: 3800lm
- Luminous efficacy: 115lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 33W

Operating device:
- Control: DALI

Certificates, Standards
- Protection rating: IP20
- Protection rating (lamp compartment, on room side): IP50
- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC

Material, Colour
- housing: aluminium, coated, pure white
- housing upper side: sheet steel, galvanised
- Cover: micro prismatic cover

Mounting
- Mounting method, mounting location: recessed, lay-in mounting, in the ceiling
- Arrangement: single arrangement
- Supplement: please order the required mounting accessories for ceiling recessing separately

Electrical connection
- Connection: terminal, 5-pole
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight
- Length: 1245mm
- Width: 307mm
- Height: 30mm
- Weight: 3.0kg

Service life
- Rated service life: 100000h (L80/B50) at AT = 25°C, 50000h (L90/B50) at AT = 25°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 17.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com