

Order No.: 5LZ930303 | GTIN (EAN): 4058352386033


Product description: SCon11,psh.bttm.interf,centCtrl



SITECO Connect 11 push button interface, central control, installation type: recessed, installation location: in the switch box, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class III (safety extra-low voltage), certification: CE, 4 x push button input, 4 x push button input, 1 x DALI-2, 1 x LED green, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1  
GTIN (EAN): 4058352386033



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 29.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5LZ930303 | GTIN (EAN): 4058352386033

Detailed technical description: SCon11,psh.bttm.interf.centCtrl



#### Key data

- System family: Siteco Connect 11
- Product type: lighting management components
- Product name: SITECO Connect 11
- Order No.: 5LZ930303

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class III (safety extra-low voltage)
- Temperature range (operation): -20..+75°C
- Certification, designation: CE

#### Material, Colour

- adapter: plastic, grey
- housing: plastic, grey
- Colour specification: grey

#### Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only suitable for indoor use

#### Dimensions, Weight

- Weight: 0.1kg

#### Inputs

##### 4x push button input

- Feature: zero-potential, cable length max. 0.5m

#### Outputs

##### 1x LED green

- Feature: for displaying initialization

Order No.: 5LZ930303 | GTIN (EAN): 4058352386033

Dimensions: SCon11,psh.btn.interf,centCtrl

