

**Order No.:** 51MP26WM2441W | **GTIN (EAN):** 4058352614686

**Product description:** Apollon<sup>®</sup> 31, 1545x200, 4600lm 840, ML, 3p



Apollon<sup>®</sup> 31, office luminaire, primary optical cover: micro prismatic cover, of PMMA, light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, LED, rated luminous flux: 4.600lm, luminous efficacy: 139lm/W, light colour: 840, colour temperature: 4000K, control gear: ECG Multilumen, with terminal, 3-pole, mains connection: 220..240V, AC, 50/60Hz, rated input power: 33W, housing, of sheet steel, coil coated, traffic white (RAL 9016), length: 1.545mm, width: 200mm, height: 44mm, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, impact resistance: IK02, permissible operating ambient temperature: -20..+40°C, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	5.3
GTIN (EAN):	4058352614686

**Order No.:** 51MP26WM2441W | **GTIN (EAN):** 4058352614686

**Detailed technical description:** Apol31,1545x200,4600lm840,ML,3p



#### Key data

- Product type: office luminaire
- Product name: Apollon® 31
- Order No.: 51MP26WM2441W

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Lighting technology:

- Cover: micro prismatic cover
- Beam angle: wide distribution, 90°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 19$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 4600lm
- Luminous efficacy: 139lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 33W

#### Operating device:

- Control gear: ECG Multilumen
- Control: ON/OFF Multilumen

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK02
- Temperature range (operation): -20...+40°C
- Certification, designation: CE

#### Material, Colour

- housing: sheet steel, coil coated, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)
- Cover: micro prismatic cover of PMMA

#### Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling
- Arrangement: single arrangement

#### Electrical connection

- Connection: terminal, 3-pole
- Nominal voltage: 220...240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 1545mm
- Width: 200mm
- Height: 44mm
- Weight: 5.3kg

#### Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C