

**Order No.:** 5DTAXTSC62002 | **GTIN (EAN):** 4058352112311

**Product description:** AXT,3ph-tr,spsurf,bk,L2000,DA



AX T, 3-phase track, installation type: suspended mounting, surface-mounted, control gear: DALI, mains connection: 220..240V/380..400V, AC, of extruded aluminium section, coated, jet black (RAL 9005), length: 2.000mm, width: 32mm, height: 33mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, packaging unit: 1 piece



Wt. (kg): 1.8  
GTIN (EAN): 4058352112311

**Order No.:** 5DTAXTSC62002 | **GTIN (EAN):** 4058352112311

**Detailed technical description:** AXT,3ph-tr,spsurf,bk,L2000,DA



#### Key data

- Product type: 3-phase track
- Product name: AX T
- Order No.: 5DTAXTSC62002

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lamps:

- Supplement: max. 16A

#### Operating device:

- Control: DALI

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, ENEC

#### Material, Colour

- Colour specification: jet black (RAL 9005)

#### Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to the ceiling

#### Electrical connection

- Nominal voltage: 220..240V/380..400V, AC

#### Dimensions, Weight

- Length: 2000mm
- Width: 32mm
- Height: 33mm
- Weight: 1.8kg