

**Order No.:** 5XA7671B0000C | **GTIN (EAN):** 4058352236406

**Product description:** FL20mn,hous,Basic,51W,IC1



Floodlight FL 20 mini, housing, primary light characteristic: asymmetric, control gear: Basic, control: power reduction, overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm<sup>2</sup>, mains connection: 220..240V, AC, rated input power: 51W, housing frame, housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, length: 446mm, width: 355mm, height: 62mm, ON/OFF, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, standard: DIN EN 12944, packaging unit: 1 piece

IP 66  

Wt. (kg): 2.9  
GTIN (EAN): 4058352236406

**Order No.:** 5XA7671B0000C | **GTIN (EAN):** 4058352236406

**Detailed technical description:** FL20mn,hous,Basic,51W,IC1



#### Key data

- Product type: housing
- Product name: Floodlight FL 20 mini
- Order No.: 5XA7671B0000C

#### Dimensions, Weight

- Length: 446mm
- Width: 355mm
- Height: 62mm
- Weight: 2.9kg

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Symmetry: asymmetric distribution

#### Lamps:

- Rated input power: 51W

#### Operating device:

- Control gear: ECG Basic
- Control: Basic
- Equipment: overheat protection, power reduction
- Switching method: electronic power reduction

#### Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Standard: DIN EN 12944
- Certification, designation: CE

#### Material, Colour

- housing frame: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- Colour specification: Siteco® metallic grey (DB 702S)

#### Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm<sup>2</sup>
- Nominal voltage: 220..240V, AC
- Surge voltage resistance: 10kV 1.2/50µs

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -