

Order No.: 5XA7671B0000C | **GTIN (EAN):** 4058352236406

Product description: FL20mn,hous,Basic,51W,IC1



Floodlight FL 20 mini, housing, primary light characteristic: asymmetric, control gear: ECG Basic, control: power reduction, overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, rated input power: 51W, housing frame, housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, length: 446mm, width: 355mm, height: 62mm, ON/OFF, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, standard: DIN EN 12944, packaging unit: 1 piece



Wt. (kg): 2.9
GTIN (EAN): 4058352236406

Order No.: 5XA7671B0000C | **GTIN (EAN):** 4058352236406

Detailed technical description: FL20mn,hous,Basic,51W,IC1



Key data

- Product type: housing
- Product name: Floodlight FL 20 mini
- Order No.: 5XA7671B0000C

Dimensions, Weight

- Length: 446mm
- Width: 355mm
- Height: 62mm
- Weight: 2.9kg

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 51W

Operating device:

- Control gear: ECG Basic
- Control: Basic
- Equipment: overheat protection, power reduction
- Switching method: electronic power reduction

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Standard: DIN EN 12944
- Certification, designation: CE, ENEC, VDE

Material, Colour

- housing frame: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- Colour specification: Siteco® metallic grey (DB 702S)

Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, AC
- Surge voltage resistance: 10kV 1.2/50µs