

**Order No.:** 51SD14EAD5A | **GTIN (EAN):** 4058352767740


**Product description:** Spot11,45°,5670lm940,DAML,90,wh



Spot 11, directional spotlight, light control with lens, of PMMA, LED rated luminous flux: 5.670lm, light colour: 940, control gear: ECG Multilumen, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, of aluminium, traffic white (RAL 9016), length: 253mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, permissible ambient temperature for indoor applications: -20..+40°C, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.9
GTIN (EAN):	4058352767740



**Order No.:** 51SD14EAD5A | **GTIN (EAN):** 4058352767740

**Detailed technical description:** Spot11,45°,5670lm940,DAML,90,wh



#### Key data

- Product type: directional spotlight
- Product name: Spot 11
- Order No.: 51SD14EAD5A

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Light control: lens of PMMA
- Beam angle: 45°
- Symmetry: symmetric
- UGR viewing direction along longitudinal luminaire axis: ≤ 16
- UGR viewing direction along lateral luminaire axis: ≤ 16

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 5670lm
- Luminous efficacy: 149lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 38W

#### Operating device:

- Control gear: ECG Multilumen
- Control: DALI Multilumen

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

#### Material, Colour

- Colour specification: traffic white (RAL 9016)

#### Mounting

- Mounting method, mounting location: slip-in mounting, in a 3-phase track

#### Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 253mm
- Diameter: 90mm
- Weight: 0.9kg

#### Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SD14EAD5A | GTIN (EAN): 4058352767740

Dimensions: Spot11,45°,5670lm940,DAML,90,wh

