

Order No.: 51SF117FB3B | GTIN (EAN): 4058352746196


Product description: Spot31SI,26°,2200lm930,0/1,wh



Spot 31 Slim, directional spotlight, light control with reflector, of aluminium, anti glare with honeycomb louvre, LED rated luminous flux: 2.200lm, light colour: 930, control gear: ECG, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, housing, of aluminium, traffic white (RAL 9016), diameter: 70mm, adapter, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.8
GTIN (EAN):	4058352746196



Order No.: 51SF117FB3B | GTIN (EAN): 4058352746196

Detailed technical description: Spot31 Sl,26°,2200lm930,0/1,wh



Key data

- Product type: directional spotlight
- Product name: Spot 31 Slim
- Order No.: 51SF117FB3B

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: reflector of aluminium
- Glare reduction: honeycomb louvre
- Beam angle: 26°
- Symmetry: symmetric
- UGR viewing direction along longitudinal luminaire axis: ≤ 25
- UGR viewing direction along lateral luminaire axis: ≤ 25

Lamps:

- Lamps: with LED
- Rated luminous flux: 2200lm
- Luminous efficacy: 96lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 90
- Light colour: 930
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 23W

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Certification, designation: CE

Material, Colour

- housing: aluminium, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)
- adapter: plastic

Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight


- Diameter: 70mm
- Weight: 0.8kg

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SF117FB3B | GTIN (EAN): 4058352746196

Dimensions: Spot31SI,26°,2200lm930,0/1,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -