


Order No.: 51SF327FB2B | GTIN (EAN): 4058352746264 Product description: Spot31SI,16°,2150Im930,0/1,bk



Spot 31 Slim, directional spotlight, light control with reflector, of aluminium, LED rated luminous flux: 2.150lm, light colour: 930, control gear: ECG, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, housing, of aluminium, jet black (RAL 9005), diameter: 70mm, adapter, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, packaging unit: 1 piece

IP 20 ≟ (∈

Lamps: LED Wt. (kg): 0.7 GTIN (EAN): 4058352746264



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

ѕітесо

Order No.: 51SF327FB2B | GTIN (EAN): 4058352746264 Detailed technical description: Spot31SI,16°,2150Im930,0/1,bk



Key data

- Product type: directional spotlight
- Product name: Spot 31 Slim
- Order No.: 51SF327FB2B

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: reflector of aluminium
- Beam angle: 16°
- Symmetry: symmetric
- UGR viewing direction along longitudinal luminaire axis: ≤ 25
- UGR viewing direction along lateral luminaire axis: ≤ 25

Lamps:

- Lamps: with LED
- Rated luminous flux: 2150lm
- Luminous efficacy: 126lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 90
- Light colour: 930
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 17W

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Certification, designation: CE

Material, Colour

- housing: aluminium, jet black (RAL 9005)
- Colour specification: jet black (RAL 9005)
- adapter: plastic

Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz,
 - AC

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Dimensions, Weight

- Diameter: 70mm
- Weight: 0.7kg


Service life

 Rated service life: 50000h (L80/B50) at AT = 25°C

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com



Order No.: 51SF327FB2B | GTIN (EAN): 4058352746264 Dimensions: Spot31SI,16°,2150lm930,0/1,bk



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -