


### Order No.: 5XMOD0155K | GTIN (EAN): 4058352780510 Product description: SL10mc,LEDmod,ST1.2a,730



Streetlight 10 micro, LED module, light distribution: ST1.2a, primary light characteristic: asymmetric, High Power LED, light colour: 730, colour temperature: 3000K, mains connection: 230..240V, 50Hz, LED module, length: 174mm, width: 137mm, height: 40mm, protection rating (complete): as luminaire, packaging unit: 1 piece


Wt. (kg): 0.8 GTIN (EAN): 405

0.8 4058352780510

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

# ѕітесо

## Order No.: 5XMOD0155K | GTIN (EAN): 4058352780510 Detailed technical description: SL10mc,LEDmod,ST1.2a,730



#### Key data

- Product type: LED module
- Product name: Streetlight 10 micro
- Order No.: 5XMOD0155K

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### Lighting technology:

- Light distribution: ST1.2a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

#### Lamps:

- Lamps: with High Power LED
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730
- Supplement: power consumption when used in Streetlight 10 Plus luminaires: construction size micro 8.5..11.5W

#### **Certificates, Standards**

- Protection rating: as luminaire

#### **Electrical connection**

- Nominal voltage: 230..240V, 50Hz

#### **Dimensions, Weight**

- Length: 174mm
- Width: 137mm
- Height: 40mm
- Weight: 0.8kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -