

Order No.: 5XC3A51U08ME | **GTIN (EAN):** 4058352856345


Product description: SL11iQmd,ST1.2a,18110lm730,SR,D4i,LSTZb



Streetlight SL 11 iQ midi, mast luminaire, primary light control with 3 zone faceted reflector, of plastic, silver coated, highly specular, primary optical cover: cover, of PMMA, transparent, light distribution: ST1.2a, light emission: direct distribution, primary light characteristic: asymmetric, installation type: post-top, side-entry, lamps: LED, High Power LED, rated values: 18.110lm | 122,7W | 147,6lm/W (begin service life); end service life: 18.110lm | 130,2W; at 50% lumin. flux: 9.055lm | 56,1W | 161,4lm/W, colour temperature: 3000K, colour rendering: CRI > 70, light colour: 730, light setting 1 begin service life: 100% | 18.110lm | 122,7W | 147,6lm/W | 3.000K, light setting 1 end service life: 130,2W, further light settings possible, control: pre-setting: logarithmic dimming characteristic, Street-Remote, Auto-Match, Temp-Guard, Lumen-Switch, Night-Set, Smart-Wire, Light-Fading, Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), optimised constant luminous flux control (CLO 2.0), with cable H07RN-F 5x 1.5mm², mains connection: 230..240V, AC, 50/60Hz, connection cable pre-assembled, cable length: 12,5m, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), please order mast flange separately, inclination adjustable without tools: 0°, 5°, 10°, 15° (post-top) | 0°, -5°, -10°, -15° (side-entry), sealing non-destructively replaceable, multi-level sealing system, length: 780mm, width: 376mm, height: 118mm, mast flange for spigot size: 42mm (side-entry): 5XC10008XM4, 60/48mm (side-entry/post-top): 5XC10108XM2, 76/60mm (side-entry/post-top): 5XC10108XM1, equipment: Power, Smart Interface below, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, ENEC+, VDE, UKCA, impact resistance: IK10, permissible operating ambient temperature for outdoor applications: -25..+50°C, standard-compliant lighting for roads and squares, Environmental Product Declaration (EPD) tested and certified by an independent institute, packaging unit: 1 piece



Lamps: LED
Wt. (kg): 11.5
GTIN (EAN): 4058352856345



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5XC3A51U08ME | **GTIN (EAN):** 4058352856345

Detailed technical description: SL11iQmd,ST1.2a,18110lm730,SR,D4i,LSTZb



Key data

- Product type: mast luminaire
- Product name: Streetlight SL 11 iQ midi
- Order No.: 5XC3A51U08ME

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated, highly specular
- Cover: cover, transparent
- Light distribution: ST1.2a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution
- Light emission: direct distribution

Lamps:

- Lamps: with High Power LED, LED
- Rated values: 18110lm | 122.7W | 147.6lm/W (begin service life); end service life: 18110lm | 130.2W; at 50% lumin. flux: 9055lm | 56.1W | 161.4lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 5 SDCM (initial)

Factory light settings (LS):

- begin service life:
LS 1: 100% | 18110lm | 122.7W | 147.6lm/W | 3000K
- end service life:
LS 1: 130.2W
- further light settings possible

Operating device:

- Control: iQ-Street Remote, D4i with power reduction, Smart Interface below
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, pre-setting: logarithmic dimming characteristic

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK10
- Temperature range (operation): -25...+50°C
- Supplement: standard-compliant lighting for roads and squares
- Certification, designation: CE, ENEC, ENEC+, VDE, UKCA
- EPD: Environmental Product Declaration (EPD) tested and certified by an independent institute

Material, Colour

- luminaire housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), please order mast flange separately, inclination adjustable without tools: 0°, 5°, 10°, 15° (post-top) | 0°, -5°, -10°, -15° (side-entry), sealing non-destructively replaceable, multi-level sealing system
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover of PMMA

Mounting

- Mounting method, mounting location: side-entry, post-top, on mast

Electrical connection

- Connection: cable H07RN-F 5x 1.5mm²
- Nominal voltage: 230...240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)
- Connection cable: pre-assembled, L= 12.5m

Dimensions, Weight

- Length: 780mm
- Width: 376mm
- Height: 118mm
- Weight: 11.5kg
- Mast spigot: mast flange for spigot size: 42mm (side-entry): 5XC10008XM4, 60/48mm (side-entry/post-top): 5XC10108XM2, 76/60mm (side-entry/post-top): 5XC10108XM1

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5XC3A51U08ME | **GTIN (EAN):** 4058352856345

Detailed technical description: SL11iQmd,ST1.2a,18110lm730,SR,D4i,LSTZb



Light emission

- Light emission: 0% at 0° inclination

Service life

- Rated service life: 100000h at AT = 25°C


It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5XC3A51U08ME | **GTIN (EAN):** 4058352856345

Dimensions: SL11iQmd,ST1.2a,18110lm730,SR,D4i,LSTZb



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -