

### Order No.: 5XMOD0175L | GTIN (EAN): 4058352780619 Product description: SL10mc,LEDmod,P1.0a,718



Streetlight 10 micro, LED module, primary light control with cycle path optic, light distribution: P1.0a, primary light characteristic: asymmetric, High Power LED, light colour: 718, colour temperature: 1800K, mains connection: 230..240V, 50Hz, LED module, length: 174mm, width: 137mm, height: 40mm, protection rating (complete): as luminaire, packaging unit: 1 piece


Wt. (kg): 0.8 GTIN (EAN): 40583

0.8 4058352780619

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

# ѕітесо

## Order No.: 5XMOD0175L | GTIN (EAN): 4058352780619 Detailed technical description: SL10mc,LEDmod,P1.0a,718



#### Key data

- Product type: LED module
- Product name: Streetlight 10 micro
- Order No.: 5XMOD0175L

# Lighting technology | Lamps | Control gear

#### **Component 1**

- Lighting technology:
- Light control: cycle path optic
- Light distribution: P1.0a
- Beam angle: extremely wide distribution
- Symmetry: asymmetric distribution

#### Lamps:

- Lamps: with High Power LED
- Colour temperature: 1800K
- Colour rendering index: CRI > 70
- Light colour: 718
- Supplement: power consumption when used in Streetlight 10 Plus luminaires: construction size micro 11.5..15.8W

#### **Certificates, Standards**

- Protection rating: as luminaire

#### **Electrical connection**

- Nominal voltage: 230..240V, 50Hz

#### **Dimensions, Weight**

- Length: 174mm
- Width: 137mm
- Height: 40mm
- Weight: 0.8kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -