

Order No.: 51MX37DA47WB | GTIN (EAN): 4058352885499

Product description: Sil21,ELD-Lwh,7300lm840,DA2,L1204,wh,sp






Silica® 21, office luminaire, primary light control with darklight reflector, of PMMA, white, CAT 2 (L≤ 3000cd/m²), light emission: direct/indirect distribution, primary light characteristic: asymmetric, installation type: suspended mounting, LED, rated luminous flux: 7.300lm, luminous efficacy: 166lm/W, light colour: 840, colour temperature: 4000K, control gear: DALI 2, with terminal, 3+2-pole, max. 2.5mm², mains connection: 220..240V, AC, 50/60Hz, rated input power: 44W, luminaire housing, of aluminium, traffic white (RAL 9016), length: 1.204mm, width: 53mm, height: 53mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, permissible operating ambient temperature: 0..+35°C, standard: EN 50419, packaging unit: 1 piece

IP 20 (≟) (∈

Lamps: LED Wt. (kg): 3.0

GTIN (EAN): 4058352885499





Order No.: 51MX37DA47WB | GTIN (EAN): 4058352885499

Detailed technical description: Sil21,ELD-Lwh,7300lm840,DA2,L1204,wh,sp



Key data

Product type: office luminaireProduct name: Silica® 21

- Order No.: 51MX37DA47WB

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: darklight reflector of PMMA, white
- Beam angle: wallwasher
- Symmetry: asymmetric distribution
- Light emission: direct/indirect distribution, 59:41
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 25

Lamps:

- Lamps: with LED

Rated luminous flux: 7300lm
Luminous efficacy: 166lm/W
Colour temperature: 4000K
Colour rendering index: CRI > 80

- Light colour: 840

 SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)

- Rated input power: 44W

Operating device:

- Control: DALI 2

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation):
 0..+35°C
- Standard: EN 50419
- Certification, designation: CE

Material, Colour

- luminaire housing: aluminium, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)

Mounting

- Mounting method, mounting location: suspended mounting
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 3+2-pole, max.
 2.5mm²
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

Length: 1204mmWidth: 53mmHeight: 53mmWeight: 3.0kg

Service life

 Rated service life: 70000h (L80/B50) at AT = 25°C, 50000h (L85/B50) at AT = 25°C



Order No.: 51MX37DA47WB | GTIN (EAN): 4058352885499

Dimensions: Sil21,ELD-Lwh,7300lm840,DA2,L1204,wh,sp

