

**Order No.: 5XCMOD2C4HC | GTIN (EAN): 4058352392089**

**Product description: SL11,Plusmnmd,LEDmod,P1.0a,740**




Streetlight SL 11 Plus mini/midi, LED module, primary light control with cycle path optic, light distribution: P1.0a, primary light characteristic: asymmetric, High Power LED, light colour: 740, colour temperature: 4000K, mains connection: 230V, 50Hz, LED module, protection rating (complete): as luminaire, packaging unit: 1 piece

Wt. (kg): 0.4  
GTIN (EAN): 4058352392089

Order No.: 5XCMOD2C4HC | GTIN (EAN): 4058352392089

**Detailed technical description:** SL11,Plusmnmd,LEDmod,P1.0a,740



#### Key data

- Product type: LED module
- Product name: Streetlight SL 11 Plus mini/midi
- Order No.: 5XCMOD2C4HC

#### Lighting technology | Lamps | Control gear

##### Component 1

###### Lighting technology:

- Light control: cycle path optic
- Light distribution: P1.0a
- Beam angle: extremely wide distribution
- Symmetry: asymmetric distribution

###### Lamps:

- Lamps: with High Power LED
- Colour temperature: 4000K
- Colour rendering index: CRI > 70
- Light colour: 740

###### Certificates, Standards

- Protection rating: as luminaire

###### Electrical connection

- Nominal voltage: 230V, 50Hz

###### Dimensions, Weight

- Weight: 0.4kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 23.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -