

Order No.: 51MQ12WD2454 | **GTIN (EAN):** 4058352928264


Product description: APO21s,M600,4200lm840,DA2ML,IP54



Apollon 21 square, office luminaire, primary optical cover: micro prismatic cover, of PMMA, CAT 2 ($L \leq 3000 \text{cd/m}^2$), light emission: direct distribution, primary light characteristic: symmetric, installation type: lay-in mounting, recessed, LED, rated luminous flux: 4.200lm, luminous efficacy: 170lm/W, light colour: 840, colour temperature: 4000K, control gear: DALI 2, Multilumen, with terminal, 5-pole, mains connection: 220..240V, AC/DC, 0/50..60Hz, rated input power: 24.7W, suitable for self-contained emergency lighting element 59MQE002602A with integrated self-test function according to EN 60598-2-22, housing, of aluminium, coated, traffic white (RAL 9016), module: M600, length: 595mm, width: 595mm, height: 55mm, recess depth: 180mm, housing upper side, of sheet steel, galvanised, protection rating (complete): IP20, protection rating (lamp compartment, on room side): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, UKCA, impact resistance: IK03, permissible operating ambient temperature: -20..+45°C, standard: EN 60598-2-22, packaging unit: 1 piece

IP 20 IK 03  

Lamps:	LED
Wt. (kg):	1.8
GTIN (EAN):	4058352928264



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 30.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51MQ12WD2454 | **GTIN (EAN):** 4058352928264

Detailed technical description: APO21s,M600,4200lm840,DA2ML,IP54



Key data

- Product type: office luminaire
- Product name: Apollon 21 square
- Order No.: 51MQ12WD2454

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: micro prismatic cover
- Beam angle: wide distribution, 90°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 19

Lamps:

- Lamps: with LED
- Rated luminous flux: 4200lm
- Luminous efficacy: 170lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 24.7W
- Supplement: with through-wiring, for emergency light function, for central battery installations according to DIN EN 60598-2-22

Operating device:

- Switching method: suitable for self-contained emergency lighting element 59MQE002602A with integrated self-test function according to EN 60598-2-22

Component 2

Certificates, Standards

- Protection rating: IP20
- Protection rating (lamp compartment, on room side): IP54
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK03
- Temperature range (operation): -20...+45°C
- Standard: EN 60598-2-22
- Certification, designation: CE, ENEC, UKCA

Material, Colour

- housing: aluminium, coated, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)
- housing upper side: sheet steel, galvanised
- Cover: micro prismatic cover of PMMA

Mounting

- Mounting method, mounting location: recessed, lay-in mounting, in the ceiling
- Arrangement: single arrangement
- Supplement: please order the required mounting accessories for ceiling recessing separately

Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220..240V, 0/50..60Hz, AC/DC

Dimensions, Weight


- Length: 595mm
- Width: 595mm
- Height: 55mm
- Recess depth: 180mm
- Weight: 1.8kg

Service life

- Rated service life: 100000h (L80/B50) at AT = 25°C, 50000h (L90/B50) at AT = 25°C

Order No.: 51MQ12WD2454 | **GTIN (EAN):** 4058352928264

Dimensions: APO21s,M600,4200lm840,DA2ML,IP54



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 30.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com