

**Order No.:** 51MQ12WC2454 | **GTIN (EAN):** 4058352928226


**Product description:** APO21s,M600,4200lm840,DA2ML,IP54



Apollon 21 square, office luminaire, primary optical cover: micro prismatic cover, of PMMA, CAT 2 ( $L \leq 3000 \text{cd/m}^2$ ), light emission: direct distribution, primary light characteristic: symmetric, installation type: lay-in mounting, recessed, LED, rated luminous flux: 4.200lm, luminous efficacy: 170lm/W, light colour: 840, colour temperature: 4000K, control gear: DALI 2, Multilumen, with terminal, 5-pole, mains connection: 220..240V, AC/DC, 0/50..60Hz, rated input power: 24.7W, suitable for self-contained emergency lighting element 59MQE002602A with integrated self-test function according to EN 60598-2-22, housing, of aluminium, coated, traffic white (RAL 9016), module: M600, length: 595mm, width: 595mm, height: 55mm, recess depth: 180mm, housing upper side, of sheet steel, galvanised, protection rating (complete): IP20, protection rating (lamp compartment, on room side): IP54, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, UKCA, impact resistance: IK03, permissible operating ambient temperature: -20..+45°C, standard: EN 60598-2-22, packaging unit: 1 piece

IP 20 IK 03  

Lamps:	LED
Wt. (kg):	1.8
GTIN (EAN):	4058352928226



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 30.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 51MQ12WC2454 | **GTIN (EAN):** 4058352928226

**Detailed technical description:** APO21s,M600,4200lm840,DA2ML,IP54



## Key data

- Product type: office luminaire
- Product name: Apollon 21 square
- Order No.: 51MQ12WC2454

## Lighting technology | Lamps | Control gear

### Component 1

#### Lighting technology:

- Cover: micro prismatic cover
- Beam angle: wide distribution, 90°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 19$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 4200lm
- Luminous efficacy: 170lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI  $> 80$
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 24.7W
- Supplement: with through-wiring, for emergency light function, for central battery installations according to DIN EN 60598-2-22

#### Operating device:

- Switching method: suitable for self-contained emergency lighting element 59MQE002602A with integrated self-test function according to EN 60598-2-22

### Component 2

## Certificates, Standards

- Protection rating: IP20
- Protection rating (lamp compartment, on room side): IP54
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK03
- Temperature range (operation): -20...+45°C
- Standard: EN 60598-2-22
- Certification, designation: CE, ENEC, UKCA

## Material, Colour

- housing: aluminium, coated, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)
- housing upper side: sheet steel, galvanised
- Cover: micro prismatic cover of PMMA

## Mounting

- Mounting method, mounting location: recessed, lay-in mounting, in the ceiling
- Arrangement: single arrangement
- Supplement: please order the required mounting accessories for ceiling recessing separately

## Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220..240V, 0/50..60Hz, AC/DC

## Dimensions, Weight


- Length: 595mm
- Width: 595mm
- Height: 55mm
- Recess depth: 180mm
- Weight: 1.8kg

## Service life

- Rated service life: 100000h (L80/B50) at AT = 25°C, 50000h (L90/B50) at AT = 25°C

**Order No.:** 51MQ12WC2454 | **GTIN (EAN):** 4058352928226

**Dimensions:** APO21s,M600,4200lm840,DA2ML,IP54



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 30.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail [info@siteco.de](mailto:info@siteco.de) • Internet [www.siteco.com](http://www.siteco.com)