

Order No.: 5EA3BGL01 | **GTIN (EAN):** 4069025002747

Product description: SConWi,MastBoxMotGPSLow



SITECO Connect Wireless Mast Box Motion GPS Low, sensor, communication: 2.4GHz, local mesh radio network, DALI, control: local setting and operation with USB stick, by movement, optionally via radio push button, by time, by timer, by weekday, with radio clock, sensor technology: GPS, 1 PIR movement sensor, Logarithmic DALI dimming curve preset. Can be switched to linear via software, installation type: surface-mounted, installation location: to mast, of plastic, voltage: 230V, voltage type: AC, GPS, radio, 2.4GHz, protection rating (complete): IP65, certification: CE, packaging unit: 1 piece, metal fastening straps not included in delivery

IP 65 CE

Wt. (kg): 0.8
GTIN (EAN): 4069025002747

Order No.: 5EA3BGL01 | **GTIN (EAN):** 4069025002747

Detailed technical description: SConWi,MastBoxMotGPSLow



Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA3BGL01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI, Logarithmic DALI dimming curve preset. Can be switched to linear via software

Certificates, Standards

- Protection rating: IP65
- Temperature range (operation): -25..+80°C
- Certification, designation: CE

Material, Colour

- housing: plastic, dark grey
- Colour specification: dark grey

Mounting

- Mounting method, mounting location: surface-mounted, to mast
- Mounting height: 0..6m

Electrical connection

- Nominal voltage: 230V, AC



Dimensions, Weight

- Weight: 0.8kg

Order No.: 5EA3BGL01 | **GTIN (EAN):** 4069025002747

Dimensions: SConWi,MastBoxMotGPSLow

Detection zone "Mast Box Motion Low"
5EA3BGL01



Mounting height	X axis	Y axis
5.0 m	8.5 m	8.8 m
6.0 m	10.2 m	10.6 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -