

Order No.: 5EA3BGH02 | GTIN (EAN): 4069025002723 Product description: SConWi,MastBoxMot2PIRGPSHigh



SITECO Connect WirelessMast Box Motion 2xPIR GPS High, sensor, communication: 2.4GHz, local mesh radio network, DALI, control: local setting and operation with USB stick, by movement, optionally via radio push button, by time, by timer, by weekday, with radio clock, sensor technology: 2 PIR movement sensors, GPS, Logarithmic DALI dimming curve preset. Can be switched to linear via software, installation type: surface-mounted, installation location: to mast, of plastic, voltage: 230V, voltage type: AC, GPS, radio, 2.4GHz, protection rating (complete): IP65, certification: CE, packaging unit: 1 piece, metal fastening straps not included in delivery

IP 65 (€

Wt. (kg): 0.8

GTIN (EAN): 4069025002723



Order No.: 5EA3BGH02 | GTIN (EAN): 4069025002723

Detailed technical description: SConWi,MastBoxMot2PIRGPSHigh



Key data

Product type: sensor

Product name: SITECO Connect

Wireless

Order No.: 5EA3BGH02

Lighting technology | Lamps | Control gear

Component 1

Operating device:

 Control: DALI, Logarithmic DALI dimming curve preset. Can be switched to linear via software

Certificates, Standards

- Protection rating: IP65
- Temperature range (operation): -25..+80°C
- Certification, designation: CE

Material, Colour

- housing: plastic, dark grey
- Colour specification: dark grey

Mounting

- Mounting method, mounting location: surface-mounted, to mast
- Mounting height: 6..12m

Electrical connection

- Nominal voltage: 230V, AC

Dimensions, Weight


- Weight: 0.8kg




Order No.: 5EA3BGH02 | **GTIN (EAN):** 4069025002723

Dimensions: SConWi,MastBoxMot2PIRGPSHigh

Detection zone "Mast Box Motion" 5EA3BGH02





Mounting heightX axisY axis5.0 - 12.0m22.0 m14.0 m

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -