

Order No.: 59LN201 | GTIN (EAN): 4058352062234 Product description: Silue21multisens,HFsens,surf



Siluette® 21, multi-sensor, installation type: surface-mounted, mains connection: 220..240V, 50/60Hz, housing, length: 149mm, height: 28mm, multi-sensor, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible operating ambient temperature: -20..+60°C, packaging unit: 1 piece

IP 20 □ (∈

Wt. (kg): 1.0

GTIN (EAN): 4058352062234



Order No.: 59LN201 | GTIN (EAN): 4058352062234

Detailed technical description: Silue21multisens,HFsens,surf

Key data

Product type: multi-sensor
Product name: Siluette® 21
Order No.: 59LN201

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+60°C
- Certification, designation: CE

Mounting

- Mounting method, mounting location: surface-mounted, to the luminaire
- Mounting height: 3m

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz

Dimensions, Weight

Length: 149mmHeight: 28mmWeight: 1.0kg

Inputs

1x HF sensor

- Connection: HF sensorDetection range: D= 10m
- Option: switching time adjustable between 5 seconds - 30 minutes
- Feature: for motion detection

1x light sensor

- Connection: light sensor
- Option: daylight threshold adjustable from 2..50lx