

**Order No.:** 5XH7B5AT08QA | **GTIN (EAN):** 4069025098320

**Product description:** SL31md,ST0.5a,21420lm830,D4i,SlA/b



Streetlight SL 31 midi D4i mast luminaire for post-top, side-entry; light control with lens of PMMA; light distribution: ST0.5a, direct asymmetric distribution, for standard-compliant lighting for roads and squares; LED: luminous flux: 21.420lm, light colour: 830, colour temperature: 3000K; luminous efficacy: 131,2lm/W; control: pre-setting: logarithmic dimming characteristic, flexible luminous flux parameterisation, time-dependent luminous flux control, constant luminous flux control, power reduction, intelligent temperature release in ECG and LED module, overheat protection; luminaire housing, of diecast aluminium, Siteco® metallic grey (DB 702S), corrosivity category C5 high according to DIN EN ISO 12944; cover of toughened safety glass, transparent, opened without tools; mast flange of diecast aluminium, Siteco® metallic grey (DB 702S), spigot size: 76/60mm, mast flange included unmounted; with cable H07RN-F 2x 1.5mm², cable length: 14,5m, connection cable pre-assembled; mains connection: 220..240V, AC, 50/60Hz; power consumption (at start of service life): 163,3W / (at end of service life): 178,2W / (with reduced operation 50%): 72,4W; protection rating (complete): IP66; insulation class (complete): insulation class II (safety insulation); impact resistance: IK09; certification: CE, ENEC, ENEC+, VDE, UKCA, ZD4i; permissible operating ambient temperature for outdoor applications: - 40..+50°C; packaging unit: 1 piece



Lamps: LED  
Wt. (kg): 10.1  
GTIN (EAN): 4069025098320



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5XH7B5AT08QA | **GTIN (EAN):** 4069025098320

**Detailed technical description:** SL31md,ST0.5a,21420lm830,D4i,SLa/b



## Key data

- Product type: mast luminaire
- Product name: Streetlight SL 31 midi
- Order No.: 5XH7B5AT08QA

## Lighting technology | Lamps | Control gear

### Component 1

#### Lighting technology:

- Light control: lens of PMMA
- Cover: cover, transparent
- Light distribution: ST0.5a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution
- Light emission: direct distribution

#### Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 21420lm
- Luminous efficacy: 131lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- Rated input power begin service life: 163
- Rated input power end service life: 178
- Rated input power at 50% lumin. flux: 72

#### Operating device:

- Control: D4i, Smart Interface below and above
- Equipment: overheat protection, power reduction, constant luminous flux control, time-dependent luminous flux control, flexible luminous flux parameterisation, intelligent temperature release in ECG and LED module, pre-setting: logarithmic dimming characteristic

## Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK09
- Temperature range (operation): -40...+50°C
- Supplement: standard-compliant lighting for roads and squares
- Corrosion protection: corrosivity category C5 high according to DIN EN ISO 12944
- Certification, designation: CE, ENEC, ENEC+, VDE, UKCA, ZD4i

## Material, Colour

- luminaire housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), sealing non-destructively replaceable, multi-level sealing system, inclination: -15°...+20° (post-top) | -20°...+20° (side-entry), adjustable in 5° steps, no sealing on luminaire upper side
- Colour specification: Siteco® metallic grey (DB 702S)
- mast flange: diecast aluminium, coated, Siteco® metallic grey (DB 702S), mast flange included unmounted
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover of toughened safety glass

## Mounting

- Mounting method, mounting location: side-entry, post-top, on mast

## Electrical connection

- Connection: cable H07RN-F 2x 1.5mm²
- Nominal voltage: 220...240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)
- Connection cable: pre-assembled, L= 14.5m

## Dimensions, Weight

- Weight: 10.1kg
- Mast spigot: spigot size: 76/60mm

## Light emission

- Light emission: 0% at 0° inclination

**Order No.:** 5XH7B5AT08QA | **GTIN (EAN):** 4069025098320

**Detailed technical description:** SL31md,ST0.5a,21420lm830,D4i,SlA/b



**Service life**

- Rated service life: 100000h (L94/B10)  
at AT = 25°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5XH7B5AT08QA | **GTIN (EAN):** 4069025098320

**Dimensions:** SL31md,ST0.5a,21420lm830,D4i,Sl a/b



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail [info@siteco.de](mailto:info@siteco.de) • Internet [www.siteco.com](http://www.siteco.com)