

Order No.: 5LZ904731A | GTIN (EAN): 4058352580318

Product description: DA2psh.bttn.interf,rec






DALI2push button interface, slave, central control - connection to lighting or building management, dimmable, installation type: recessed, installation location: in the switch box, of plastic, protection rating (complete): IP20, certification: CE, 4 x push button input, 1 x DALI-2, packaging unit: 1 piece

IP 20 (€

Wt. (kg): 0.1

GTIN (EAN): 4058352580318





# Order No.: 5LZ904731A | GTIN (EAN): 4058352580318 Detailed technical description: DA2psh.bttn.interf,rec



#### Key data

- System family: Siteco Connect 11, SITECO Connect 21
- Product type: push button interface
- Product name: DALI2Order No.: 5LZ904731A

## Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: DALI 2, dimmable

#### Certificates, Standards

- Protection rating: IP20
- Temperature range (operation): 0..+50°C
- Certification, designation: CE

#### Material, Colour

- housing: plastic, grey
- Colour specification: grey

#### Mounting

- Mounting method, mounting location: recessed, in the switch box
- Supplement: only suitable for use in indoor areas

#### **Dimensions, Weight**

Length: 42mmWidth: 42mmHeight: 20mmWeight: 0.1kg

#### Inputs

#### 4x push button input

- Connection: cable pair (2-pole),
  A=0.25mm², colour coding of cables,
  with pre-assembled wire end sleeve
- Feature: maximum of 4 potential-free push buttons can be connected

#### Outputs

#### 1x DALI-2

- Connection: plug-in terminal, 2-pole, max. 2.5mm<sup>2</sup>
- System current: 6mA



### Order No.: 5LZ904731A | GTIN (EAN): 4058352580318

Dimensions: DA2psh.bttn.interf,rec

