

Order No.: 5XA1565E1V3 | **GTIN (EAN):** 4069025123343

Product description: GT,ST1.2a,730,asy,cvr.pan,TSG,transp



electrics components group, for Large Bell iQ, LED luminous flux: 4.750 lm, colour temperature: 3000K, mains connection: 220..240V, AC, 50/60Hz, start of lifetime: 34 W, end of service life: 38 W, reduction: 16 W, primary light characteristic: asymmetric, primary optical cover: cover panel, of toughened safety glass, transparent, gear tray with cover, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE



Lamps:	LED
Wt. (kg):	4.0
GTIN (EAN):	4069025123343

Order No.: 5XA1565E1V3 | **GTIN (EAN):** 4069025123343

Detailed technical description: GT,ST1.2a,730,asy,cvr.pan,TSG,transp

Key data

- Product type: electrics components group
- Product name: Large Bell iQ
- Order No.: 5XA1565E1V3

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated
- Cover: cover panel, transparent
- Light distribution: ST1.2a
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 4750lm
- Luminous efficacy: 139lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730
- Rated input power begin service life: 34
- Rated input power end service life: 38
- Rated input power at 50% lumin. flux: 16

Operating device:

- Control: iQ-Street Remote, D4i with power reduction, Smart Interface above
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, pre-setting: logarithmic dimming characteristic

Certificates, Standards

- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

Material, Colour

- Cover: cover panel of toughened safety glass

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

Dimensions, Weight

- Weight: 4.0kg

Light emission

- Light emission: < 3%