

Order No.: 5XA1575E1F | GTIN (EAN): 4069025073846

Product description: GT,ST1.2a,730,asy





electrics components group, for Small Bell iQ, luminous flux: 3.220 lm, colour temperature: 3000K, mains connection: 230..240V, AC, 50/60Hz, start of lifetime: 20 W, end of service life: 21 W, reduction: 10 W, primary light characteristic: asymmetric, gear tray, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE



Wt. (kg): 1.6

GTIN (EAN): 4069025073846



# Order No.: 5XA1575E1F | GTIN (EAN): 4069025073846

# **Detailed technical description:** GT,ST1.2a,730,asy



# Key data

- Product type: electrics components group
- Product name: Small Bell iQOrder No.: 5XA1575E1F

# Lighting technology | Lamps | Control gear

## Component 1

### Lighting technology:

- Light control: 3 zone facetted reflector of plastic, silver coated
- Light distribution: ST1.2aBeam angle: wide distribution
- Symmetry: asymmetric distribution

#### Lamps:

- Lamps: with High Power LED
- Rated luminous flux: 3220lm
- Luminous efficacy: 160lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730
- Rated input power begin service life: 20
- Rated input power end service life: 21
- Rated input power at 50% lumin. flux:
  10

## Operating device:

- Control: iQ Street-Remote
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, pre-setting: logarithmic dimming characteristic

#### **Certificates, Standards**

- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

#### **Electrical connection**

- Nominal voltage: 230..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

#### **Dimensions, Weight**

- Weight: 1.6kg

## Light emission

- Light emission: < 3%