

**Order No.:** 51TP11DN59XG | **GTIN (EAN):** 4069025331922

**Product description:** Lic11Pr,nrrw,9100lm850,DA2,IP64,L1500,wh



Licross® 11 Protected MO, luminaire insert, of sheet steel, galvanised, coil coated, white, length: 1.500mm, width: 90mm, height: 101mm, LED rated luminous flux: 9.100lm, light colour: 850, control gear: DALI 2, with plug, 5-pole, with phase selection, mains connection: 220..240V, AC, 50/60Hz, rated input power: 53W, internal wiring halogen-free, primary light control with lens, of plastic, primary optical cover: cover, of PMMA, light emission: direct distribution, primary light characteristic: symmetric, protection rating (complete): IP64, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, protection symbol: D if used in an environment with conductive dust loads with corresponding accessories, impact resistance: IK06, permissible ambient temperature for indoor applications: -25...+35°C, LABS conformity tested according to VDMA 24364:2018-05, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, packaging unit: 1 piece



|             |               |
|-------------|---------------|
| Lamps:      | LED           |
| Wt. (kg):   | 2.4           |
| GTIN (EAN): | 4069025331922 |



**Order No.:** 51TP11DN59XG | **GTIN (EAN):** 4069025331922

**Detailed technical description:** Lic11Pr,nrrw,9100lm850,DA2,IP64,L1500,wh



## Key data

- Product type: luminaire insert
- Product name: Licross® 11 Protected MO
- Order No.: 51TP11DN59XG

## Lighting technology | Lamps | Control gear

### Component 1

#### Lighting technology:

- Light control: lens of plastic
- Cover: cover
- Beam angle: narrow distribution
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 22$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 9100lm
- Luminous efficacy: 173lm/W
- Colour temperature: 5000K
- Colour rendering index: CRI  $> 80$
- Light colour: 850
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 2$  SDCM (initial)
- Rated input power: 53W
- Supplement: internal wiring halogen-free

#### Operating device:

- Control: DALI 2

## Certificates, Standards

- Protection rating: IP64
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK06
- Protection symbol: D if used in an environment with conductive dust loads with corresponding accessories
- Temperature range (operation): -25...+35°C
- Supplement: corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, LABS conformity tested according to VDMA 24364:2018-05
- Certification, designation: CE, ENEC, VDE, UKCA

## Material, Colour

- Licross® LED insert: sheet steel, galvanised, coil coated, white
- Colour specification: white
- Cover: cover of PMMA

## Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail
- Arrangement: single/continuous arrangement
- Supplement: only suitable for use in indoor areas

## Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 220...240V, 50/60Hz, AC

## Dimensions, Weight

- Length: 1500mm
- Width: 90mm
- Height: 101mm
- Weight: 2.4kg

## Service life

- Rated service life: 100000h (L95/B50) at AT = 25°C, 100000h (L90/B50) at AT = ta max

**Order No.:** 51TP11DN59XG | **GTIN (EAN):** 4069025331922

**Dimensions:** Lic11Pr,nrrw,9100lm850,DA2,IP64,L1500,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 11.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -