

Order No.: 5LZ930REM1 | GTIN (EAN): 4069025335197 Product description: SCon11rem.rout,netw.ETH,rec

SITECO Connect 11, LTE remote maintenance router, installation type: recessed, control: Bluetooth 4.0, mains connection: 230V, AC, 50/60Hz, housing, of plastic, black, LTE remote maintenance router, M2M LTE SIM card inserted and prepared. Includes setup, configuration, and portal maintenance costs. Included are a power supply, antenna, and a DIN rail adapter, protection rating (complete): IP20, protection rating (on room side): IP21, certification: CE, packaging unit: 1 piece

IP 20 (E

Wt. (kg): 0.1 GTIN (EAN): 4069025335197

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 06.06.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 5LZ930REM1 | GTIN (EAN): 4069025335197 Detailed technical description: SCon11rem.rout,netw.ETH,rec

Key data

- System family: Siteco Connect 11
- Product type: LTE remote maintenance router
- Product name: SITECO Connect 11
- Order No.: 5LZ930REM1

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Equipment: Bluetooth 4.0

Certificates, Standards

- Protection rating: IP20
- Protection rating (on room side): IP21
- Certification, designation: CE

Material, Colour

- housing: plastic, black
- Colour specification: black

Mounting

 Mounting method, mounting location: recessed, in an electrical distributor

Electrical connection

- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Weight: 0.1kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 06.06.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -