


Order No.: 5LZ904002A | **GTIN (EAN):** 4069025312204

Product description: DA2repea,DALI,rec




DALI2repeater, master, central control - connection to lighting or building management, dimmable, installation type: recessed, installation location: in the luminaire, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, UKCA, voltage: 110..230V, voltage type: AC, 1 x DALI, 1 x TouchDim input, 1 x DALI broadcast, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1
GTIN (EAN): 4069025312204

Order No.: 5LZ904002A | **GTIN (EAN):** 4069025312204

Detailed technical description: DA2repea,DALI,rec



Key data

- System family: Siteco Connect 11, SITECO Connect 21
- Product type: repeater
- Product name: DALI2
- Order No.: 5LZ904002A

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0...+50°C
- Certification, designation: CE, UKCA

Material, Colour

- housing: plastic, grey
- housing: plastic, grey
- Colour specification: grey

Mounting

- Mounting method, mounting location: recessed, in the luminaire
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: terminal, 2-pole, max. 1.5mm²
- Nominal voltage: 110...230V, 50/60Hz, AC

Dimensions, Weight

- Length: 118mm
- Width: 30mm
- Height: 21mm
- Weight: 0.1kg

Inputs

1x DALI

- Connection: plug-in terminal, 2-pole, max. 1.5mm²

1x TouchDim input

- Connection: plug-in terminal, 1-pole, max. 1.5mm²

Outputs

1x DALI broadcast

- Connection: plug-in terminal, 2-pole, max. 1.5mm²
- Limiting: max. 64x ECG DALI
- System current: max. 130mA
- Cable length: max. 300m