


Order No.: 58DC011D02300A | GTIN (EAN): 4069025391612

**Product description:** LunR,LI,wd,4400lm830,DA2



Lunis R, luminaire insert, rated luminous flux: 4.400lm, light colour: 830, control gear: DALI 2, mains connection: 220..240V, AC, 50/60Hz, rated input power: 27W, primary light control with lens, of plastic, primary optical cover: cover, of PMMA, light emission: direct distribution, protection rating (complete): IP20, certification: CE, packaging unit: 1 piece

IP 20 CE

Wt. (kg): 0.5  
GTIN (EAN): 4069025391612

Order No.: 58DC011D02300A | GTIN (EAN): 4069025391612

Detailed technical description: LunR,LI,wd,4400lm830,DA2



#### Key data

- Product type: luminaire insert
- Product name: Lunis R
- Order No.: 58DC011D02300A

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Lighting technology:

- Light control: lens of plastic
- Cover: cover
- Beam angle: wide distribution
- Light emission: direct distribution

#### Lamps:

- Rated luminous flux: 4400lm
- Luminous efficacy: 164lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- Rated input power: 27W

#### Operating device:

- Control: DALI 2

#### Certificates, Standards

- Protection rating: IP20
- Certification, designation: CE

#### Material, Colour

- Quantity: 1 piece
- Cover: cover of PMMA

#### Mounting

- Arrangement: single arrangement

#### Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Weight: 0.5kg