


Order No.: 5LZ904350A | GTIN (EAN): 4069025427014

Product description: DA2sens,PIR-sens,rec



DALI2sensor PR3, slave, central control - connection to lighting or building management, dimmable, installation type: recessed, installation location: in the luminaire, of plastic, protection rating (complete): IP20, certification: CE, UKCA, 1 x PIR movement sensor, 1 x light sensor, 1 x DALI, 1 x LED red/green, packaging unit: 1 piece

IP 20 

Wt. (kg): 0.1
GTIN (EAN): 4069025427014

Order No.: 5LZ904350A | **GTIN (EAN):** 4069025427014

Detailed technical description: DA2sens,PIR-sens,rec



Key data

- System family: DALI-2
- Product type: sensor
- Product name: DALI2
- Order No.: 5LZ904350A

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Temperature range (operation): -20..+50°C
- Certification, designation: CE, UKCA

Material, Colour

- housing: plastic, white
- Colour specification: white

Mounting

- Mounting method, mounting location: recessed, in the luminaire
- Mounting height: 2..5m
- Supplement: only suitable for use in indoor areas

Dimensions, Weight

- Length: 48mm
- Width: 15mm
- Height: 19mm
- Weight: 0.1kg

Inputs

1x PIR movement sensor

- Connection: PIR sensor (passive-infrared)
- Detection angle: 360°
- Detection range: tangential max. 4x4m
- Detection range: max. 2x 2m
- Option: detection range can be limited in stages using extendable lens covers (2x 180°)
- Feature: rectangular detection area

1x light sensor

- Illuminance: 20..800lx (directly at sensor)

Outputs

1x DALI

- System current: max. 6mA

1x LED red/green

- Feature: for displaying initialization