


Order No.: 51TD16DN4AXG3S | **GTIN (EAN):** 4069025479495


Product description: Lic11Pe,wd,10110lm840,DA2,IP54,L1500,wh



Licross® 11 Performance MO, luminaire insert, of sheet steel, galvanised, coil coated, white, length: 1.500mm, width: 120mm, height: 123mm, LED rated luminous flux: 10.110lm, light colour: 840, SDCM (Standard Deviation of Colour Matching)MacAdam ≤ 2 SDCM (initial), control gear: DALI 2, with plug, 6-pole, with phase selection, for trunking rail, 14-core, mains connection: 220..240V, AC, 50/60Hz, rated input power: 61W, for emergency light function, internal wiring halogen-free, for trunking rail, 14-core, converter,control gear: single battery element, battery: LiFePO4, 9Ah, primary light control with lens, of plastic, primary optical cover: cover, of PMMA, light emission: direct/indirect distribution, primary light characteristic: symmetric, protection rating (complete): IP54, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories, impact resistance: IK06, permissible ambient temperature for indoor applications: +5..+35°C, standard: EN 60598-2-22, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, LABS conformity tested according to VDMA 24364:2018-05, packaging unit: 1 piece

IP 54 IK 06  

Lamps:	LED
Wt. (kg):	2.9
GTIN (EAN):	4069025479495



Order No.: 51TD16DN4AXG3S | **GTIN (EAN):** 4069025479495

Detailed technical description: Lic11Pe,wd,10110lm840,DA2,IP54,L1500,wh



Key data

- Product type: luminaire insert
- Product name: Licross® 11
Performance MO
- Order No.: 51TD16DN4AXG3S

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Cover: cover
- Beam angle: wide distribution
- Symmetry: symmetric
- Light emission: direct/indirect distribution, 80:20
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 22

Lamps:

- Supplement: with self-test function according to EN 60598-2-22, 2-rod battery, charging phase on R (wire number 6)

Operating device:

- Control gear: single battery element
- Battery: LiFePO4
- Nominal operating time: 3h

Component 2

Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK06
- Protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories
- Temperature range (operation): $+5..+35^{\circ}\text{C}$
- Supplement: corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, LABS conformity tested according to VDMA 24364:2018-05
- Standard: EN 60598-2-22
- Certification, designation: CE, UKCA

Material, Colour

- Licross® LED insert: sheet steel, galvanised, coil coated, white
- Colour specification: white
- Cover: cover of PMMA

Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail
- Arrangement: single/continuous arrangement
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 6-pole, with phase selection, for trunking rail, 14-core
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 1500mm
- Width: 120mm
- Height: 123mm
- Weight: 2.9kg

Service life

- Rated service life: 100000h (L95) at AT = 25°C , 100000h (L90) at AT = $t_{a\text{ max}}$

Order No.: 51TD16DN4AXG3S | **GTIN (EAN):** 4069025479495

Dimensions: Lic11Pe,wd,10110lm840,DA2,IP54,L1500,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 22.08.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -