

**Order No.:** 51SD147AW2B | **GTIN (EAN):** 4058352678169


**Product description:** Spot21Pe,wd,2800lmWHR,0/1,90,wh



Spot 21 Performance, directional spotlight, light control with reflector, of aluminium, beam angle: wide distribution, LED rated luminous flux: 2.800lm, light colour: White Effect, control gear: ECG, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, housing, of aluminium, white, diameter: 90mm, adapter, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, packaging unit: 1 piece

IP 20  

|             |               |
|-------------|---------------|
| Lamps:      | LED           |
| Wt. (kg):   | 0.8           |
| GTIN (EAN): | 4058352678169 |



Order No.: 51SD147AW2B | GTIN (EAN): 4058352678169

Detailed technical description: Spot21Pe,wd,2800lmWHR,0/1,90,wh



#### Key data

- Product type: directional spotlight
- Product name: Spot 21 Performance
- Order No.: 51SD147AW2B

#### Lighting technology | Lamps | Control gear

##### Component 1

#### Lighting technology:

- Light control: reflector of aluminium
- Beam angle: wide distribution
- Symmetry: symmetric

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 2800lm
- Colour rendering index: CRI > 90
- Light colour: White Effect

#### Operating device:

- Control gear: ECG
- Control: ON/OFF

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Certification, designation: CE

#### Material, Colour

- housing: aluminium, white
- adapter: plastic

#### Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Diameter: 90mm
- Weight: 0.8kg

#### Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SD147AW2B | GTIN (EAN): 4058352678169

Dimensions: Spot21Pe,wd,2800lmWHR,0/1,90,wh

